



Multipair Individually Screened Cables-Belden Equivalent 8777

» Application


These cables have individually screened pairs laid up. Each individually screened pair has a 22AWG stranded tinned copper drain wire. These cables are suitable for use as audio, control and computer cables.

» Construction

- » Conductor: Tinned copper wire.
- » Insulation: PP.
- » Individual Screen: Aluminium/

Polyester tape.

- » Drain Wire: Tinned copper wire.
- » Sheath: PVC (V type)/LSZH (H type).
- » Insulation Colour: Red & Black, Black & White, Black & Green.



» Electrical & Mechanical Characteristics

| | | |
|---------------------------------------------------|------|---------------------|
| AWG | | 22 |
| Conductor Construction | | 7x0.254 |
| UL Style | | 2919 |
| Maximum Conductor Resistance | Ω/km | 54.8 |
| Voltage Rating | V | 30 |
| Nominal Capacitance Conductor to Conductor | pF/m | 98 |
| Nominal Capacitance Conductor to Screen | pF/m | 180 |
| Bending Radius | | 10xOverall Diameter |
| Operating Temperature | °C | -20~80 |

» Dimensions

| Ordering Code | No. of Pairs | Insulation Thickness | Sheath Thickness | Overall Diameter |
|---------------|--------------|----------------------|------------------|------------------|
| | | mm | mm | mm |
| BE118777V | 3 | 0.25 | 0.86 | 6.9 |
| BE118777H | 3 | 0.25 | 0.86 | 6.9 |