



Multipair Individually Screened Cables-Belden Equivalent 8778

» Application

These cables have individually screened pairs laid up. Each individually screened pair has a 22AWG stranded tinned copper drain wire. These cables are used as computer cables.

» Construction


- » Conductor: Tinned copper wire.
- » Insulation: PP.
- » Individual Screen: Aluminium/

Polyester tape.

- » Drain Wire: Tinned copper wire.

- » Sheath: PVC (V type)/LSZH (H type).

» Insulation Colour: Black & Red, Black & White, Black & Green, Black & Blue, Black & Yellow, Black & Brown.



» Electrical & Mechanical Characteristics

AWG		22
Conductor Construction		7x0.254
UL Style		2919
Maximum Conductor Resistance	Ω/km	54.8
Voltage Rating	V	30
Nominal Capacitance Conductor to Conductor	pF/m	98
Nominal Capacitance Conductor to Screen	pF/m	180
Bending Radius		10xOverall Diameter
Operating Temperature	$^{\circ}\text{C}$	-20~80

» Dimensions

Ordering Code	No. of Pairs	Insulation Thickness	Sheath Thickness	Overall Diameter
		mm	mm	mm
BE118778V	6	0.25	1.22	9.6
BE118778H	6	0.25	1.22	9.6