



Multipair Individually Screened Cables-Belden Equivalent 9879

» Application

These cables have individually screened pairs laid up. Each individually screened pair has a 22AWG stranded tinned copper drain wire. These cables are used as computer cables.


» Construction

- » Conductor: Tinned copper wire.
- » Insulation: PP.
- » Individual Screen: Aluminium/

Polyester tape.

- » Drain Wire: Tinned copper wire.
- » Sheath: PVC (V type)/LSZH (H type).

» Insulation Colour: Black & Red, Black & White, Black & Green, Black & Blue, Black & Yellow, Black & Brown, Black & Orange, Red & White, Red & Green, Red & Blue, Red & Yellow, Red & Brown, Red & Orange, Green & White, Green & Blue.



- PVC/LSZH Sheath
- Stranded Tinned Copper Conductor
- PP Insulation
- Individual Aluminium/Polyester Tape
- Stranded Drain Wire

» Electrical & Mechanical Characteristics

AWG		20
Conductor Construction		7x0.32
UL Style		2919
Maximum Conductor Resistance	Ω/km	34.1
Voltage Rating	V	30
Nominal Capacitance Conductor to Conductor	pF/m	98
Nominal Capacitance Conductor to Screen	pF/m	180
Bending Radius		10xOverall Diameter
Operating Temperature	°C	-20~80

» Dimensions

Ordering Code	No. of Pairs	Insulation Thickness	Sheath Thickness	Overall Diameter
		mm	mm	mm
BE119879V	15	0.33	1.22	17.6
BE119879H	15	0.33	1.22	17.6