



Date: 27 Aug 2009

Part No.: PP79951

0.6/1KV Multi-core

Mica & XLPE Insulated Steel Wire Armored LSZH Jacket Cable

Application:

Power cables are multi conductor cables which convey low energy electrical signals used for monitoring or controlling electrical power systems and their associated processes. Instrumentation cables convey signals from process monitors to process analyzers (usually electronics equipment) and from the analyzers to control equipment in the electric power system.

Construction:

Conductor: Stranded plain copper conductor.

Insulation: Conductors are insulated with Mica fire resisting tape and XLPE.

Inner Jacket: LSZH compound

Armor: Galvanized steel wire armor

Sheathing: An outer protection of Flame Retardant LSZH compound is applied over the armor. Sheath color: Black.

Standard: IEC60331, BS6387

Packing: The cables are delivered on non-returnable wood drums.

Mechanical Properties:

Voltage rating: 0.6/1kV

Temperature rating -15°C to 90 °C

Bending radius (static): Circular conductor $r = 6D$
Shaped conductor $r = 8D$

Minimum bending radius during installation: 12 x Overall Diameter

Flexibility: Rigid



Caledonian

Marchants Industrial Centre,
Mill Lane, Laughton, Lewes,
East Sussex, BN8 6AJ, UK
Tel: +44 (0) 1273 478736
Fax: +44 (0) 1273 473682

88 Connaught Road West,
16/FguangdongFinanceBuilding,
HongKong
Tel: + 852 2116 1238
Fax: + 852 2803 0726

Cable Size:

No. of Cores	Thickness of insulation nom. (mm)	Diameter under armor nom. (mm)	Nominal steel armor wire diameter nom. (mm)	Thickness of over sheath nom. (mm)	Overall Diameter approx. (mm)
2.5mm ²					
21	0.7	39.6	2.0	2.2	48.0

The data included in the present catalogue are merely indicative; Caledonian Cables Limited reserves to itself the right to change them as its own discretion in any time.